



Material Information Sheet

Jerico Plastic Ind. Inc.

January 2015

Material Type: **RF 08 Flame Retardant**

ALL COLORS

PROPERTIES	ASTM	ENGLISH UNIT
MELT INDEX	D-1238	4.0G/10 MIN
DENSITY	D-1505	1.0 G/CC
TESILE .125"THICK	D-638	2100PSI
FLEXURAL MODULUS 1% STRAIN	D-790	90,000PSI
ARM LOW IMPACT 0.125" SPECIMEN	ARM METHOD	25FT/LB

FOR YOUR PROTECTION

THE INFORMATION AND RECOMMENDATIONS IN THIS PUBLICATION ARE TO THE BEST OF OUR KNOWLEDGE AND ARE RELIABLE. SUGGESTIONS CONCERNING USES OR APPLICATIONS ARE ONLY THE OPINION OF JERICO PLASTIC INDUSTRIES, INC. AND USERS SHOULD MAKE THEIR OWN TESTS TO DETERMINE THE SUITABILITY OF THIS PRODUCT FOR THEIR PARTICULAR PURPOSES. HOWEVER, BECAUSE OF NUMEROUS FACTORS AFFECTING RESULTS, JERICO PLASTIC INDUSTRIES, INC. MAKES NO WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED. INCLUDING THOSE OF MERCHANTABILITY AND FITNESS PURPOSES OTHER THAT THE MATERIAL CONFORMS TO ITS APPLICABLE CURRENT STANDARD SPECIFICATIONS. STATEMENTS HEREIN SHOULD NOT BE CONSTRUED AS REPRESENTATIONS OF WARRENTIES. THE RESPONSIBILTY OF JERICO PLASTIC INDUSTRIES, INC FOR CLAIMS ARISING OUT OF BREECH WARRANTY, NEGLIGENCE, STRICT LIABILITY, OR OTHERWISE IS LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.