



Material Information Sheet

Jerico Plastic Ind. Inc.

January 2015

Material Type: **SL9467 COLORS**

| <b>PROPERTIES</b>                 | <b>ASTM</b> | <b>ENGLISH UNIT</b> |
|-----------------------------------|-------------|---------------------|
| MELT INDEX                        | D-1238      | 7.0G/10 MIN         |
| DENSITY                           | D-1505      | .946G/CC            |
| TESILE .125" THICK                | D-638       | 2,950PSI            |
| FLEXURAL MODULUS<br>1% STRAIN     | D-790       | 128,000PSI          |
| ARM LOW IMPACT<br>0.125" SPECIMEN | ARM METHOD  | 55FT/LB             |

FOR YOUR PROTECTION

THE INFORMATION AND RECOMMENDATIONS IN THIS PUBLICATION ARE TO THE BEST OF OUR KNOWLEDGE AND ARE RELIABLE. SUGGESTIONS CONCERNING USES OR APPLICATIONS ARE ONLY THE OPINION OF JERICO PLASTIC INDUSTRIES, INC. AND USERS SHOULD MAKE THEIR OWN TESTS TO DETERMINE THE SUITABILITY OF THIS PRODUCT FOR THEIR PARTICULAR PURPOSES. HOWEVER, BECAUSE OF NUMEROUS FACTORS AFFECTING RESULTS, JERICO PLASTIC INDUSTRIES, INC. MAKES NO WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED. INCLUDING THOSE OF MERCHANTABILITY AND FITNESS PURPOSES OTHER THAN THAT THE MATERIAL CONFORMS TO ITS APPLICABLE CURRENT STANDARD SPECIFICATIONS. STATEMENTS HEREIN SHOULD NOT BE CONSTRUED AS REPRESENTATIONS OF WARRANTIES. THE RESPONSIBILITY OF JERICO PLASTIC INDUSTRIES, INC FOR CLAIMS ARISING OUT OF BREACH WARRANTY, NEGLIGENCE, STRICT LIABILITY, OR OTHERWISE IS LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.