



# Jerico Plastic Industries, Inc.

## RS 9355

### Product Information

---

The RS 9355 is a general purpose linear low density polyethylene. This compound offers quick cycles and lot by lot consistency. The RS 9355 has good flow and stiffness. Compound is UV stabilized.

### General Information

---

Material Status	- Commercial: Active
Availability	- North America
Additive	- UV Stabilizer
Features	- Fast Molding Cycle, UV Stabilized, Good Flow
Uses	- General
Appearance	- Black and Colors Available
Forms	- Pellets and Powder
Processing Method	- Rotational Molding

### Physical Information

### English Unit

### Test Method

---

Melt Index	5.0G/10 MIN	ASTM D-1238
Density	.935G/CC	ASTM D-1505
Tensile .125"	2,400 PSI	ASTM D-638
Flexural Modulus 1% Strain	85,000 PSI	ASTM D-790
Arm Cold (-40°F) Temperature Impact 0.125" Specimen	60FT/LB.	ARM METHOD -40°C
Elongation/Break	700%	2"/MIN D-638
ESCR F50 100% IGEPAL	>1,000	ASTM D-1693 COND A
Deflection Temp (66 PSI)	125°F	ASTM D-648

---

### FOR YOUR PROTECTION

THE INFORMATION AND RECOMMENDATIONS IN THIS PUBLICATION ARE TO THE BEST OF OUR KNOWLEDGE AND ARE RELIABLE. SUGGESTIONS CONCERNING USES OR APPLICATIONS ARE ONLY THE OPINION OF JERICO PLASTIC INDUSTRIES, INC. AND USERS SHOULD MAKE THEIR OWN TESTS TO DETERMINE THE SUITABILITY OF THIS PRODUCT FOR THEIR PARTICULAR PURPOSES. HOWEVER, BECAUSE OF NUMEROUS FACTORS AFFECTING RESULTS, JERICO PLASTIC INDUSTRIES, INC. MAKES NO WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED. INCLUDING THOSE OF MERCHANTABILITY AND FITNESS PURPOSES OTHER THAN THAT THE MATERIAL CONFORMS TO ITS APPLICABLE CURRENT STANDARD SPECIFICATIONS. STATEMENTS HEREIN SHOULD NOT BE CONSTRUED AS REPRESENTATIONS OF WARRANTIES. THE RESPONSIBILITY OF JERICO PLASTIC INDUSTRIES, INC FOR CLAIMS ARISING OUT OF BREACH WARRANTY, NEGLIGENCE, STRICT LIABILITY, OR OTHERWISE IS LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.