



Jerico Plastic Industries, Inc.

RS 9415

Product Information

The RS 9415 is a high quality hexene linear medium density polyethylene designed for rotational molding and can be used in projects that require good stiffness, flow, and toughness.

General Information

Material Status	Commercial: Active
Availability	North America
Additive	UV Stabilizer
Appearance	Natural Color, available also in compounded colors
Forms	Powder
Processing Method	Rotational Molding
Uses	Industrial Tanks and Septic Tanks
Features	Strong, UV Resistant, and Good Impact

Physical Information

English Unit

Test Method

	<u>English Unit</u>	<u>Test Method</u>
Melt Index	4.0/10 MIN	ASTM D-1238
Density	.941G/CC	ASTM D-1505
Tensile .125" Thick	3,100 PSI	ASTM D-638
Flexural Modulus 1% Strain	100,000	ASTM D-790
Arm Cold (-40°F) Temperature Impact 0.125" Specimen	55FT/LB.	ARM METHOD

FOR YOUR PROTECTION

THE INFORMATION AND RECOMMENDATIONS IN THIS PUBLICATION ARE TO THE BEST OF OUR KNOWLEDGE AND ARE RELIABLE. SUGGESTIONS CONCERNING USES OR APPLICATIONS ARE ONLY THE OPINION OF JERICO PLASTIC INDUSTRIES, INC. AND USERS SHOULD MAKE THEIR OWN TESTS TO DETERMINE THE SUITABILITY OF THIS PRODUCT FOR THEIR PARTICULAR PURPOSES. HOWEVER, BECAUSE OF NUMEROUS FACTORS AFFECTING RESULTS, JERICO PLASTIC INDUSTRIES, INC. MAKES NO WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED. INCLUDING THOSE OF MERCHANTABILITY AND FITNESS PURPOSES OTHER THAN THAT THE MATERIAL CONFORMS TO ITS APPLICABLE CURRENT STANDARD SPECIFICATIONS. STATEMENTS HEREIN SHOULD NOT BE CONSTRUED AS REPRESENTATIONS OF WARRANTIES. THE RESPONSIBILITY OF JERICO PLASTIC INDUSTRIES, INC FOR CLAIMS ARISING OUT OF BREACH WARRANTY, NEGLIGENCE, STRICT LIABILITY, OR OTHERWISE IS LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.