



# Jerico Plastic Industries, Inc.

## **RS 9422**

### **Product Information**

---

The RS 9422 has long term UV stabilization and has good flow in tank or similar large part applications. This product also has good toughness and great impact. This material is suited for large tank applications.

### **General Information**

---

Material Status	- Commercial: Active
Availability	- North America
Additive	- Long Term UV Stabilizer
Appearance	- Black and Colors Available
Forms	- Pellets and Powder
Processing Method	- Rotational Molding

### **Physical Information**

### **English Unit**

### **Test Method**

---

Melt Index	2.3G/10 MIN	ASTM D-1238
Density	.942 G/CC	ASTM D-1505
Tensile .125" Thick	2,700 PSI	ASTM D-638
Flexural Modulus 1% Strain	120,000 PSI	ASTM D-790
Arm Cold (-40°F) Temperature Impact 0.125" Specimen	55 FT/LB.	ARM METHOD
Ultimate Elongation	200	ASTM D-638

---

### FOR YOUR PROTECTION

THE INFORMATION AND RECOMMENDATIONS IN THIS PUBLICATION ARE TO THE BEST OF OUR KNOWLEDGE AND ARE RELIABLE. SUGGESTIONS CONCERNING USES OR APPLICATIONS ARE ONLY THE OPINION OF JERICO PLASTIC INDUSTRIES, INC. AND USERS SHOULD MAKE THEIR OWN TESTS TO DETERMINE THE SUITABILITY OF THIS PRODUCT FOR THEIR PARTICULAR PURPOSES. HOWEVER, BECAUSE OF NUMEROUS FACTORS AFFECTING RESULTS, JERICO PLASTIC INDUSTRIES, INC. MAKES NO WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED. INCLUDING THOSE OF MERCHANTABILITY AND FITNESS PURPOSES OTHER THAN THE MATERIAL CONFORMS TO ITS APPLICABLE CURRENT STANDARD SPECIFICATIONS. STATEMENTS HEREIN SHOULD NOT BE CONSTRUED AS REPRESENTATIONS OF WARRANTIES, OR RESPONSIBILITY OF JERICO PLASTIC INDUSTRIES, INC FOR CLAIMS ARISING OUT OF BREACH WARRANTY, NEGLIGENCE, STRICT LIABILITY, OR OTHERWISE IS LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.